

# Micro-Ohm Meters

## MRM Series, 10-200 Amp

### Testing Applications

Accurately measure very low contact resistances of breakers, switches, busbars, motors, generators, or any application where low resistance current is required.

### Safety and Design Features

- Microprocessor controlled
- 4-wire Kelvin measurement
- Easy to read digital screen display
- IEC safety compliant
- Separate Cable/Accessory carrying case

### Models Available

- MRM-10
- MRM-100A
- MRM-10E
- MRM-200

- **Lightweight** and **ruggedly constructed**
- **Reliable** and **accurate** measurements in the **laboratory** or in the **field**
- Printable test results via **external printer** or **built-in printer**



**Model MRM-10**  
10 Amps




**Model MRM-10E**  
10 Amps with enhanced accuracy



**Model MRM-100A**  
100 Amps



**Model MRM-200**  
200 Amps



MODEL	MRM-10	MRM-10E	MRM-100A	MRM-200
TEST CURRENT	1 mA - 10 A	1 mA - 10 A	up to 100 A (True DC)	5 A - 200 A (True DC)
RESISTANCE RANGES	0-2000 $\mu\Omega$ @ 10 A 0-20 m $\Omega$ @ 10 A 0-200 m $\Omega$ @ 1 A 0-2000 m $\Omega$ @ 100 mA 0-20 $\Omega$ @ 10 mA 0-200 $\Omega$ @ 1 mA	0-2000 $\mu\Omega$ @ 10 A 0-20 m $\Omega$ @ 10 A 0-200 m $\Omega$ @ 1A 0-2000 m $\Omega$ @ 100 mA 0-20 $\Omega$ @ 10 mA 0-200 $\Omega$ @ 1 mA	0.1 $\mu\Omega$ to 300 m $\Omega$	0.1 $\mu\Omega$ to 2 m $\Omega$ , with 0.1 $\mu\Omega$ resolution 2 m $\Omega$ to 200 m $\Omega$ , with 10 $\mu\Omega$ resolution 200 m $\Omega$ to 1 $\Omega$ , with 1 m $\Omega$ resolution
RESOLUTION	1 $\mu\Omega$ @ 10 A	0.1 $\mu\Omega$ @ 10A	up to 0.1 $\mu\Omega$	up to 0.1 $\mu\Omega$
INPUT	100-240 V, 50/60 Hz	100-240 V, 50/60 Hz	100-240 V, 50/60 Hz	100-240 V, 50/60 Hz
BASIC ACCURACY	$\pm$ (0.2% of reading $\pm$ 2 digits)	$\pm$ (0.1% of reading + 0.005% of full scale)	$\pm$ (1% of reading $\pm$ 1 digit)	$\pm$ 1% of measured value
PROTECTION	n/a	n/a	Overcurrent, short-circuit and thermal	Overcurrent, short-circuit and thermal
OPERATING TEMPERATURE	-5°C to 50°C	-5°C to 50°C	-5°C to 50°C	-5°C to 50°C
STORAGE TEMPERATURE	-25°C to 65°C	-25°C to 65°C	-10°C to 60°C	-10°C to 60°C
HUMIDITY	<90%, non-condensing	<90%, non-condensing	<90%, non-condensing	<90%, non-condensing
ADVANCED FEATURES	Powered by rechargeable battery Measured value display hold function	Powered by rechargeable battery Measured value display hold function	Programmable set-up test time 5-120 seconds Software w/automatic report generator, including operator's comments Built-in memory with capacity to store 50 registers with 80 readings each Built-in Printer	Programmable set-up test time 5-120 seconds Software w/automatic report generator, including operator's comments Built-in memory with capacity to store 50 registers with 80 readings each
DIMENSIONS				
Length	15" (378 mm)	15" (378 mm)	20" (502 mm)	20" (502 mm)
Width	12" (308 mm)	12" (308 mm)	15.5" (394 mm)	15.5" (394 mm)
Height	7" (175 mm)	7" (175 mm)	7.5" (190 mm)	7.5" (190 mm)
WEIGHT	19 lbs (8.7 kgs)	17 lbs (7.6 kgs)	45 lbs (20.5 kgs)	45 lbs (20.5 kgs)
ACCESSORIES Included	2 Combined test leads (current and potential) 1 Charger Power cord 1 RS232 cable User guide 1 Synthetic bag for cables and instrument	2 Combined test leads (current and potential) 1 Charger Power cord 1 RS232 cable User guide 1 Synthetic bag for cables and instrument	2 Combined test leads (current and potential) 1 Ground cable 1 Power cord 1 USB Communication cable 1 Carrying case for the test leads 1 Software license User guide	2 Combined test leads (current and potential) 1 Ground cable 1 Power cord 1 USB Communication cable 1 Carrying case for the test leads 1 Software license User guide



## PHENIX TECHNOLOGIES

### WORLD HEADQUARTERS

**Phenix Technologies, Inc.**  
75 Speicher Drive  
Accident, MD 21520 USA  
Ph: +1.301.746.8118  
Fx: +1.301.895.5570  
Info@phenixtech.com

### BRANCH OFFICES

#### Phenix Systems AG

Riehenstrasse 62A, 4058 Basel, Switzerland  
Ph: +41.61.383.2770, Fx: +41.61.383.2771, Info@phenixsystems.com

#### Phenix Asia

Zhong Cheng Rd, Sec 1, No 177, 2F, Taipei 11148 Taiwan  
Ph: +886.2.2835.9738, Fx: +886.2.2835.9879, Info@phenixasia.com

