

Ground Jumper Tester

Model JT-200



Testing Applications

The JT-200 Ground Jumper Tester is designed to perform in-service testing of temporary grounding jumper assemblies used on de-energized electric power lines and equipment as specified by ASTM Standard 2249-03.

The test set is equipped with separate voltage sensing leads to avoid problems related to contact resistance between the test set and jumper under test.

The voltage tables have been developed based on values given in ASTM Standard 2249-03 and the Terman formula for calculating loop inductance. It is possible to test more complex jumper assemblies if the voltage drop at 200 A across them is known by adding this number to that obtained from the table.

- **Portable, Lightweight**
- **Simple set-up and operation**
- **Ruggedly constructed** for years of **field and shop use**

Safety and Design Features

- Main power circuit breaker
- On/Off pushbutton switches
- Backup circuit breaker for regulator/transformer protection
- Output via interchangeable terminals with voltage sense leads
- Zero-start interlock
- Operation/maintenance manual





INPUT		120 VAC, 60 Hz, Single Phase 5 Amps
OUTPUT		0-3 VAC, 200 Amps
DIGITAL METERING	Type / Accuracy	3 ½ digit, 1% of reading ± 5 counts
	Voltmeter Range	0-3 VAC
	Currentmeter Range	0-200 AAC
DIMENSIONS & WEIGHT	Length	20" (508 mm)
	Width	16" (406 mm)
	Height	9" (229 mm)
	Weight	45 lbs. (20 kgs)



PHENIX TECHNOLOGIES

WORLD HEADQUARTERS

Phenix Technologies, Inc.
75 Speicher Drive
Accident, MD 21520 USA
Ph: +1.301.746.8118
Fx: +1.301.895.5570
Info@phenixtech.com

BRANCH OFFICES

Phenix Systems AG
Riehenstrasse 62A, 4058 Basel, Switzerland
Ph: +41.61.383.2770, Fx: +41.61.383.2771, Info@phenixsystems.com

Phenix Asia
Zhong Cheng Rd, Sec 1, No 177, 2F, Taipei 11148 Taiwan
Ph: +886.2.2835.9738, Fx: +886.2.2835.9879, Info@phenixasia.com



ISO
9001:2008
Compliant