

# Current Transformer Tester

## Model CTT-5



### Testing Applications

The CTT-5 will test the Current Transformer Ratio, Phase Shift, Polarity, Excitation, Saturation, Winding Resistance and Insulation Resistance using the voltage method in compliance with ANSI/IEEE C57.13.1 & IEC 60044-1 standards, where voltage is applied to the secondary X terminals of the current transformer. The CTT-5 burden test injects a current into the secondary loop to verify the integrity of the current circuit and to determine its impedance and VA. This information is required to insure the CT will perform under all circumstances.

### Design Features

- High resolution color display allows operator to create and save repeatable test plans
- All tests are performed in automatic sequence without the need for operator intervention
- Rugged design to meet the most demanding field testing environments
- Large internal memory (200 testing files where each can have of up to 10 excitation curves and 140 test plans files)
- All CT nameplate and equipment details are stored with the test result file
- Built-in thermal printer
- Full QWERTY keyboard for easy on-site data entry
- 2000 VAC saturation test voltage with knee point voltage markers (ANSI 10/50, IEC 60044, IEEE 30 and IEEE 45)
- Fast full testing operation. Manual mode is available for trouble shooting and special diagnostic testing.
- Burden mode makes it possible to analyze the secondary circuit connected to the CT
- Easy setup of test plans are created on the instrument
- Convenient integrated test leads storage compartment
- Automatic test report creation
- User selectable time duration for insulation resistance test (10 to 60 seconds)
- Automatic demagnetization sequence

- High resolution **color** display
- All **tests** are performed in **automatic sequence without** the need for **operator intervention**
- **Rugged** design to meet the most **demanding** field testing **environments**
- **Large internal memory**
- Full **QWERTY keypad** for easy data entry



The CTT-5 is a rugged and easy to use current transformer tester that offers automatic and manual testing modes. The instrument is designed to deliver fast and reliable measurements.



## Specifications

<b>Power input</b>	115 ± 10% 60 Hz
<b>Fuse rating</b>	15 A or 8 A , 250 VAC, Type F
<b>Voltage output</b>	0-50 V / 0-200 V / 0-600 V @ 2 A 0-1200 V @ 1.5 A, 0-2000 V @ 1.2 A
<b>Voltage reading</b>	In three ranges, up to 1999.9 V ± 0.1%
<b>Current reading</b>	0 to 1.9999 A RMS ± 0.5%
<b>Ratio and accuracy</b>	0.80 to 1000:1 ± 0.5% 1000 to 2000:1 ± 0.5% 2000 to 5000:1 ± 1% 5000 to 10000:1 ± 1%
<b>Measurement method</b>	ANSI / IEEE C57.13.1, IEC-60044-1
<b>Phase angle</b>	±180°/ 0.0 to 359.9° ±1°
<b>Winding resistance</b>	0-1.9999 ohms ± 1%, 2-19.999 ohms ± 1%
<b>Insulation resistance</b>	2 M to 1 G-ohms ±3%
<b>Current source</b>	0-20 A @ 20 VAC Continuous
<b>Current source display</b>	19.999 A rms ±1% 19.999 Vrms ± 1%, 1 Mohm to 1000 ohms
<b>Data storage</b>	Up to 200 files with up to 10 excitation curves per file
<b>Test plans</b>	Up to 140 test plans
<b>X Inputs</b>	Multiplexer with five X inputs accommodates test on CT with up to 4 windings without disconnecting and connecting test leads during the test.
<b>Display</b>	4¾" x 3½" (120 mm x 90 mm) bright color LCD display
<b>Printer</b>	40 characters, 3.12" (80 mm) commercial thermal paper, paper support
<b>Housing</b>	Rugged, waterproof to IP-67 / NEMA 6 with wheels and retractable extension handle.
<b>Operating temperature</b>	-10°C to +50°C (+14°F to +122°F)
<b>PC connection</b>	USB, RS-232C, USB memory stick
<b>Dimensions</b>	18 1/2" (470 mm) L x 14" (356 mm) W x 7 1/2" (190 mm) H
<b>Weight</b>	55 lbs (24.94 kgs)
<b>Memory Stick</b>	100 MB+
<b>Approvals</b>	EN 61010:2001 EN 61326-1:1997 Class A

## Standard Accessories

- X test leads, 20' (6 m)
- H test leads, 35' (10 m)
- Burden test leads, 18' (5 m)
- Ground lead, 15' (4.5 m)
- Main input power cord
- Serial communication cable
- USB communication cable
- Spare rolls of printer paper
- CD with report manager software
- User manual



## Optional Equipment

- CTT-5 shipping case
- CTT-5 printer paper roll
- Custom made test clips
- Custom length test leads



**PHENIX**  
**TECHNOLOGIES**

### WORLD HEADQUARTERS

**Phenix Technologies, Inc.**  
75 Speicher Drive  
Accident, MD 21520 USA  
Ph: +1.301.746.8118  
Fx: +1.301.895.5570  
Info@phenixtech.com

### BRANCH OFFICES

**Phenix Systems AG**  
Riehenstrasse 62A, 4058 Basel, Switzerland  
Ph: +41.61.383.2770, Fx: +41.61.383.2771, Info@phenixsystems.com

**Phenix Asia**  
Zhong Cheng Rd, Sec 1, No 177, 2F, Taipei 11148 Taiwan  
Ph: +886.2.2835.9738, Fx: +886.2.2835.9879, Info@phenixasia.com

ISO  
9001:2008  
Compliant

