



Benchtop AC Dielectric Test Sets

5-15 kV

- Single-piece, benchtop and floor models
- Housed in a rugged steel enclosure
- Optimum safety features and simple operation



Model 605-2P



Model 615-20P


TESTING APPLICATIONS

- Suitable for AC dielectric and insulation testing up to 15 kV on all types of electrical products such as motors, cables, switchgear, bushings, capacitors, fuses, and arrestors
- Complies with UL, CSA, OSHA, NEMA, IEC, AEIC, EPCEA, IEEE, ASTM and other applicable testing standards

The Phenix line of 5 kV-15 kV AC Hipots offer a completely integrated, easy-to-use high voltage AC supply. The air insulated high voltage transformer, controls and regulator are housed either in a painted steel benchtop enclosure or for the larger units in a free-standing steel enclosure.

All units are equipped with standard safety features such as circuit breaker protection, adjustable output overloads, external interlock provisions, and zero start interlock. The digital meters display a direct reading of the output voltage and current. The output voltage is completely adjustable from near zero to 100% of output via a rugged and reliable variable autotransformer.

These AC dielectric test systems are ideally suited for dielectric testing up to 15kVAC within a wide variety of applications.



	MODEL	605-2P	605-5P	605-10P	610-2P
INPUT	Voltage	115/120 V, 60 Hz or	220/240 V	220/240 V	115/120 V, 60 Hz or
	Frequency	220/240 V, 50 Hz	50/60 Hz	50/60 Hz	220/240 V, 50 Hz
OUTPUT	Voltage	≈ 0-5 kV	≈ 0-5 kV	≈ 0-5 kV	≈ 0-10 kV
	Current	0-400 mA	0-1 A	0-2 A	0-200 mA
DUTY CYCLES	5 min ON/15 min OFF	2 kVA	5 kVA	10 kVA	2 kVA
OPTION BURN	Rating	1 kVA	1 kVA	3 kVA	1 kVA

	MODEL	610-10P	610-20P	615-10P	615-20P
INPUT	Voltage	220/240 V	220/240 V	220/240 V	220/240 V
	Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
OUTPUT	Voltage	≈ 0-10 kV	≈ 0-10 kV	≈ 0-15 kV	≈ 0-15 kV
	Current	0-1 A	0-2 A	0-667 mA	0-1.33 A
DUTY CYCLES	5 min ON/15 min OFF	10 kVA	20 kVA	10 kVA	20 kVA
OPTION BURN	Rating	3 kVA	3 kVA	3 kVA	3 kVA

DIMENSIONS & WEIGHT / SHIPPING SIZE – consult factory

SAFETY & DESIGN FEATURES

- One-piece design
- Circuit breaker protection
- External interlock provision
- External warning circuit provision
- Latching HV On/Off pushbuttons
- Zero Start Interlock
- Manual control of output voltage
- Adjustable overload circuit
- Slow and fast-acting transient protection on all meters and relays
- Digital Meters (3 1/2 digit LCD display)
- Digital Timer with audible alarm
- Emergency Off pushbutton
- Output overload indicator with reset switch
- Casters mounted on cabinets (excludes -2P models)
- Input power cable 5' (1.5 m) and shielded output cable 15' (4.5 m) are included
- Operation/maintenance manual

ENVIRONMENTAL CONDITIONS

- 10-40°C, indoor/outdoor in fair weather
- Humidity <95% non-condensing
- Altitude <3300 ft (1000 meters)

OPTIONS

- **Flashing Light**
- **Safety Foot Switch**
- **Custom cable lengths**
- **Burn Feature**
The Burn Feature is a current limiting device that is connected in series with the primary winding. This feature offers the ability to burn the faults in the test specimen at a controlled current level. The Burn Feature is available with rating listed above.

High Voltage • High Current • High Power Test Systems and Components

**ISO 9001
CERTIFIED**



www.phenixtech.com

World Headquarters
Phenix Technologies, Inc.
 75 Speicher Drive
 Accident, MD 21520 USA
Ph: +1.301.746.8118
Fx: +1.301.895.5570
Info@phenixtech.com

Branch Offices

Phenix Systems AG
 Riehenstrasse 62A, 4058 Basel, Switzerland
Ph: +41.61.383.2770 • Fx: +41.61.383.2771
Info@phenixsystems.com

Phenix Asia
 Zhong Cheng Rd, Sec 1, No 177, 2F, Taipei 11148 Taiwan
Ph: +886.2.2835.9738 • Fx: +886.2.2835.9879
Info@phenixasia.com

